

ELECTRONICS

TECHNICAL BULLETIN

Date: May 18, 2001 NO.: 2001-08

TITLE: DCS Compact SIO Pin Configuration

The purpose of this bulletin is to correct the documentation regarding the serial cable connections on the MISC 1 and MISC 2 cards for the DCS Compact KSU. The diagrams in the DCS Compact Technical Manual Installation section (Figure 7-7 and 7-8 dated June 1995) should be changed to reflect the following pin configurations:

Figure 7-7: PIN CONNECTIONS FOR THE MISC CARD TO A PERSONAL COMPUTER

	MISC Card (DB9)	PC (DB9)	PC (DB25)
TXD	pin 2	pin 3	pin 2
RXD	pin 3	pin 2	pin 3
GND	pin 7	pin 5	pin 7
DTR	pin 5	pin 4	pin 20

Figure 7-8: PIN CONNECTIONS FOR THE MISC CARD TO A MODEM

	Misc Card (DB9)	Modem (DB25)
TXD	pin 2	pin 3
RXD	pin 3	pin 2
GND	pin 7	pin 7

Note:

This bulletin replaces TB-9804 and TB-9901. The manual will be updated effective July 1, 2001

If you have any questions about this or any other Technical bulletins please contact Technical support by phone 1(800) 737-7008 or by email techsupportmiami@sta.samsung.com.